



DURASIL SMOOTH

Durasil Smooth; It is an acrylic based, silicone added, water-based, smooth, glue-free matte finish ply coating material which is used for protective and decorative purposes on external surfaces and especially used on acrylic putty applied surfaces.

It is decorative with its different colors.

DURABLE

Because it contains high quality silicone additives; resistant to climatic conditions; Waterproof, do not swell, do not fade.

USAGE

- Plaster
- Pasted Surfaces
- Concrete Surfaces of Prefabricated Constructions
- Primed Metal Surfaces
- Old Painted Surfaces

APPLICATION

Before starting the paint application, the cement in the new plaster and concrete surfaces should be waited for 4 weeks to be painted. Surface and air temperature should not be less than + 5 °C at the time of application.

In order to prevent sudden water loss of the paint to be applied to the wall and to ensure better adherence to the surface, approximately 5 kg. diluted with water 1 kg. Durapaint Primer by brush or roller until the surface is saturated. Acrylic Paste for the repair of minor defects in the wall; used Duracrack for the repair of deep errors.

The surfaces prepared for painting should be applied with roller by diluting about 20% with water and waiting for 2 hours and 12 hours between the layers.

Top surface drying is 12 hours at 20 °C and 65% humidity. 36 hours is required for full drying and impact resistance.

MATERIAL CONSUMPTION

Primer: 20 - 30 g / m²

Durasil Smooth: 400-500 g / m²

STORAGE

The material must be stored in cool and frost-free places. It is not recommended to keep the packing material for more than 24 months.

Durasil Smooth is available in 20 kg cans which can be stored on top of each other.